

Drum Mower

PZ 170

Product Information



www.KuhnNorthAmerica.com



The 5'5" cutting width of the KUHN PZ 170 drum mower provides small-acreage landowners and hay producers with significantly improved capacity and productivity compared to sicklebar mowers. This drum mower easily cuts through tall, thick and tangled grasses with minimal horsepower required. Designed to be reliable and simple to operate, the PZ 170 builds on a legacy that goes back over 50 years to the introduction of the world's first drum mowers.



Flat-Sided Drums

The flat sides of the drums are the key to moving cut crop off the drums and through the machine with minimal risk of blockage. The drum and drum skirt are separate detachable parts, which reduces repair costs and downtime.



Rotating Skids

The large surface area and free rotation of the skids greatly reduce the drag of the mower over the ground while protecting the stubble and turf. The skids also provide outstanding flotation over uneven ground.



Fast-Fit Blades

Using the special tool provided with the machine, you can easily push the blade holder down and replace the blades. This is a proven, quick and efficient system with no additional tools required.



Work to Transport and Back

A simple rope-controlled pin is used to lock the mower in the rearward transport position. The mower head is swung by hand from the transport position to the side working position or back to the transport position. A hydraulic vertical fold option is also available.



Safety Breakaway System

Upon encountering an obstacle, the breakaway releases and the mower unit pivots back to protect the mower. The breakaway is easily reset by reversing the tractor and returning the mower to the working position.



Flotation Spring

A flotation spring reduces the weight of the mower unit on the ground to improve mower flotation and terrain following.

Technical Specifications

Drum Mower

PZ 170

Working Width	65" (1.65 m)
Transport Width	55" (1.4 m)
Hitch	Cat. 1 & 2
Number of Drums	2
Number of Knives Per Drum	3
Cutting Height Adjustment	Shims & Top Link
Fast-Fit Blades	Standard
Swath Wheel	Optional
Hydraulic Vertical Fold	Optional
Adapter for Wide Tractor	Optional
PTO Speed	540
Weight	838 lbs. (380 kg)
Tractor Hydraulics	Not Required with Standard Equipment
Minimum PTO Power Requirement	27 hp (10 kW)



KUHN NORTH AMERICA, INC.

Corporate Headquarters
1501 West Seventh Avenue - Brodhead, WI 53520

Our machines comply with the North American safety regulations. In our leaflets, to better illustrate certain details of the machines some safety devices could have been removed. Conforming to the assembly and operator's manual, in no circumstances must machine be operated without these safety devices in place. All machines are equipped with safety devices which comply with the regulations of the countries in which they are delivered. In the interest of progress, we reserve the right to change without notice any specifications, design or materials listed. Patents filed in several countries.

Find us on

